

Brand	SILVERLINE
Model	SM1162-60 RF
Annual Energy Consumption (AEC)(kWh/a)	100
Energy Efficiency Class (EEI)	D
Fluid Dynamic Efficiency(FDE)	14,7
Fluid Dynamic Efficiency class (FDE) (Indice)	D
Light Efficiency (LE)	5
Lighting Efficiency Class (LE)(indice)	F
Grease Filtering Efficiency (GFE)	80,0
Grease Filtering Efficiency Class (GFE)(indice)	C
Minimum Air Flow in Normal Use MIN (m ³ /h)	268
Maximum Air Flow in Normal Use (intensive / boost excluded) MAX (m ³ /h)	530
Air Flow at Intensive/Boost Setting (m ³ /h)	-
Sound Power Level at Minimum Speed Available in Normal Use MIN (L _{WA})(dB)	51
Sound Power Level at Maximum Speed Available in Normal Use MAX (L _{WA})(dB)	65
Sound Power Level at Intensive/Boost Setting (L _{WA})(dB)	-
Power Consumption Off Mode (P _o)(W)	0,60
Power Consumption in Standby Mode (P _s)(W)	-
Product Information compliant to commission regulation (EU) No 66/2014	
Time increase factor (f)	1,5
Energy Efficiency (EELhood)	91,0
Measured air flow rate at best efficiency point (Q _{BEP})(m ³ /h)	270,0
Measured air pressure at best efficiency point (P _{BEP})(Pa)	260
Measured electric power input at best efficiency point (W _{BEP})(W)	132,0
Nominal power of the lighting system (W _L)(W)	40,0
Average illumination of the lighting system on the cooking surface (E _{middle})(lux)	190