Directive EU 65/2014 – EN61591, EN60704-2-13, EN50554	
SILVERLINE CONTROL OF THE STATE	
Model SM3379-60 SR	1
Annual Energy Consumption (AEC)(kWh/a)	51
inergy Efficiency Class (EEI)	Α
luid Dynamic Efficiency(FDE)	31,9
luid Dynamic Efficiency class (FDE) (Indice)	Α
ight Efficiency (LE)	45
ighting Efficiency Class (LE)(indice)	Α
Grease Filtering Efficiency (GFE)	76,1
Grease Filtering Efficiency Class (GFE)(indice)	С
Ainimum Air Flow in Normal Use MIN (m³/h)	294
Aaximum Air Flow in Normal Use (intensive / boost excluded) MAX (m³/h)	604
nir Flow at Intensive/Boost Setting (m³/h)	-
ound Power Level at Minimum Speed Avaible in Normal Use MIN (LWA)(dB)	53
ound Power Level at Maximum Speed Avaible in Normal Use MAX (LWA)(dB)	70
ound Power Level at Intensive/Boost Setting (LWA)(dB)	-
Power Consuption Off Mode (Po)(W)	-
ower Consuption in Standby Mode (Ps)(W)	0,80
Product Information compliant to commission regulation (EU) No 66/2014	•
ime increase factor (f)	0,9
inergy Efficiency (EElhood)	50,5
Neasured air flow rate at best efficiency point (QBEP)(m³/h)	366,0
Neasured air pressure at best efficiency point (PBEP)(Pa)	467
Aeasured electric power input at best efficiency point (WBEP)(W)	149,0
lominal power of the lighting system (WL)(W)	6,0
overage illumination of the lighting system on the cooking surface (Emiddle)(lux)	268