Directive EU 65/2014 – EN61591, EN60704-	2-13, EN50554
Brand	SILVERLINE
Model	SM3379-80 SR
Annual Energy Consumption (AEC)(kWh/a)	50
Energy Efficiency Class (EEI)	Α
Fluid Dynamic Efficiency(FDE)	33,1
Fluid Dynamic Efficiency class (FDE) (Indice)	Α
Light Efficiency (LE)	35
Lighting Efficiency Class (LE)(indice)	A
Grease Filtering Efficiency (GFE)	76,0
	С
Grease Filtering Efficiency Class (GFE)(indice)	276
Minimum Air Flow in Normal Use MIN (m³/h)	276
Maximum Air Flow in Normal Use (intensive / boost excluded) MAX (m³/h)	620
Air Flow at Intensive/Boost Setting (m³/h)	660
Count Double Level at Minimum Count Augitals in Normal Line MIN (1999)	53
Sound Power Level at Minimum Speed Avaible in Normal Use MIN (LWA)(dB)	67
Sound Power Level at Maximum Speed Avaible in Normal Use MAX (LwA)(dB)	07
Sound Power Level at Intensive/Boost Setting (LWA)(dB)	71
Power Consuption Off Mode (Po)(W)	-
	0,80
Power Consuption in Standby Mode (Ps)(W) Product Information compliant to commission re	
r rouget morniation compliant to commission re	Salution (20) 110 00/2014
Time increase factor (f)	0,8
	48,6
Energy Efficiency (EElhood)	
Measured air flow rate at best efficiency point (QBEP)(m³/h)	358,7
	F01
Measured air pressure at best efficiency point (PBEP)(Pa)	501
	150,8
Measured electric power input at best efficiency point (WBEP)(W)	7.0
Nominal power of the lighting system (WL)(W)	7,0
	245
Average illumination of the lighting system on the cooking surface (Emiddle)(lux) 3379.8 480.01	