Directive EU 65/2014 – EN61591, EN60	
Brand	SILVERLINE COLOR COLOR
Model	SM 3391-80SR OPAL 52
Annual Energy Consumption (AEC)(kWh/a)	
Energy Efficiency Class (EEI)	Α
Fluid Dynamic Efficiency(FDE)	29,6
Fluid Dynamic Efficiency class (FDE) (Indice)	Α
Light Efficiency (LE)	44
Lighting Efficiency Class (LE)(indice)	A
Grease Filtering Efficiency (GFE)	70,0
Grease Filtering Efficiency Class (GFE)(indice)	D
Minimum Air Flow in Normal Use MIN (m³/h)	229
Maximum Air Flow in Normal Use (intensive / boost excluded) MAX (m³/h]	582
Air Flow at Intensive/Boost Setting (m³/h)	750
Sound Power Level at Minimum Speed Avaible in Normal Use MIN (LWA)(d	42 dB)
Sound Power Level at Maximum Speed Avaible in Normal Use MAX (LWA)(	dB) 64
Sound Power Level at Intensive/Boost Setting (LWA)(dB)	67
Power Consuption Off Mode (Po)(W)	-
Power Consultion in Standby Mode (PS)(M)	0,22
Power Consuption in Standby Mode (Ps)(W)  Product Information compliant to commission r	egulation (EU) No 66/2014
, , , , , , , , , , , , , , , , , , ,	
Time increase factor (f)	0,9
Energy Efficiency (EElhood)	53,0
Energy Emiliency (EEmilood)	
Measured air flow rate at best efficiency point (QBEP)(m³/h)	338,2
	454
Measured air pressure at best efficiency point (PBEP)(Pa)	
Management all activity accounts in the table of finite and a circle (MDCD)(M)	144,0
Measured electric power input at best efficiency point (WBEP)(W)	6,5
Nominal power of the lighting system (WL)(W)	202
Average illumination of the lighting system on the cooking surface (Emiddle	e)(lux) 283