Directive EU 65/2014 – EN61591, EN60704-2-13, EN50554	4
Brand SILVERLINI	
Model SM 3391-9	
Annual Energy Consumption (AEC)(kWh/a)	52
Energy Efficiency Class (EEI)	A
Fluid Dynamic Efficiency(FDE)	29,6
Fluid Dynamic Efficiency class (FDE) (Indice)	Α
Light Efficiency (LE)	44
Lighting Efficiency Class (LE)(indice)	Α
Grease Filtering Efficiency (GFE)	70,0
Grease Filtering Efficiency Class (GFE)(indice)	D
Minimum Air Flow in Normal Use MIN (m³/h)	229
Maximum Air Flow in Normal Use (intensive / boost excluded) MAX (m ³ /h)	582
Air Flow at Intensive/Boost Setting (m³/h)	750
Sound Power Level at Minimum Speed Avaible in Normal Use MIN (LWA)(dB)	42
Sound Power Level at Maximum Speed Avaible in Normal Use MAX (LWA)(dB)	64
Sound Power Level at Intensive/Boost Setting (LWA)(dB)	67
Power Consuption Off Mode (Po)(W)	-
Power Consuption in Standby Mode (Ps)(W)	0,22
Product Information compliant to commission regulation (EU) No 66	/2014
Time increase factor (f)	0,9
Energy Efficiency (EElhood)	53,0
Measured air flow rate at best efficiency point (QBEP)(m ³ /h)	338,2
Massurad air prossura at host officiency point (DPED)/Da)	454
Measured air pressure at best efficiency point (PBEP)(Pa) Measured electric power input at best efficiency point (WBEP)(W)	144,0
Nominal power of the lighting system (WL)(W)	6,5
Average illumination of the lighting system on the cooking surface (Emiddle)(lux)	283