Directive EU 65/2014 – EN61591, EN60	0704-2-13, EN50554
Brand	SILVERLINE
Model	SM 3410-60 SR INT APOLLO
Annual Energy Consumption (AEC)(kWh/a)	55,0
Energy Efficiency Class (EEI)	В
Fluid Dynamic Efficiency(FDE)	24,1
Fluid Dynamic Efficiency class (FDE) (Indice)	В
Light Efficiency (LE)	81
Lighting Efficiency Class (LE)(indice)	A
Grease Filtering Efficiency (GFE)	75,5
Grease Filtering Efficiency Class (GFE)(indice)	С
Minimum Air Flow in Normal Use MIN (m³/h)	254
Maximum Air Flow in Normal Use (intensive / boost excluded) MAX (m³/h)	511
Air Flow at Intensive/Boost Setting (m³/h)	-
Sound Power Level at Minimum Speed Avaible in Normal Use MIN (LWA)(dl	<b>52</b>
Sound Power Level at Maximum Speed Avaible in Normal Use MAX (LWA)(c	dB) 67
Sound Power Level at Intensive/Boost Setting (LWA)(dB)	-
Power Consuption Off Mode (Po)(W)	-
Power Consuption in Standby Mode (Ps)(W)	0,45
Product Information compliant to commission r	egulation (EU) No 66/2014
Time increase factor (f)	1,1
Energy Efficiency (EElhood)	61,9
Measured air flow rate at best efficiency point (QBEP)(m³/h)	266,2
Wiedsdred dif flow face at best emelency point (QDEF)(iii /ii)	422
Measured air pressure at best efficiency point (PBEP)(Pa)	423
	129,7
Measured electric power input at best efficiency point (WBEP)(W)	4,0
Nominal power of the lighting system (WL)(W)	325
Average illumination of the lighting system on the cooking surface (Emiddle	