| Directive EU 65/2014 – EN61591, EN60704-2-13, EN50564                             |          |
|---|----------|
| Brand SILVERLINE  Model SL 4117 - 80 RF BETA ADA                                  |          |
| Model SL 4117 - 80 RF   | BETA ADA |
| Annual Energy Consumption (AEC)(kWh/a)  | 48,1     |
| Energy Efficiency Class (EEI)   | Α        |
| Fluid Dynamic Efficiency(FDE)   | 30,0     |
| Fluid Dynamic Efficiency class (FDE) (Indice)                                     | Α        |
| Light Efficiency (LE)   | 64       |
| Lighting Efficiency Class (LE)(indice)  | Α        |
| Grease Filtering Efficiency (GFE)   | 76,0     |
| Grease Filtering Efficiency Class (GFE)(indice)                                   | С        |
| Minimum Air Flow in Normal Use MIN (m³/h)   | 248      |
| Maximum Air Flow in Normal Use (intensive / boost excluded) MAX (m³/h)            | 642      |
| Air Flow at Intensive/Boost Setting (m³/h)  | -        |
| Sound Power Level at Minimum Speed Avaible in Normal Use MIN (LWA)(dB)            | 45       |
| Sound Power Level at Maximum Speed Avaible in Normal Use MAX (LWA)(dB)            | 66       |
| Sound Power Level at Intensive/Boost Setting (LWA)(dB)                            | -        |
| Power Consuption Off Mode (Po)(W)   | 0,40     |
| Power Consuption in Standby Mode (Ps)(W)  | -        |
| Product Information compliant to commission regulation (EU) No 66/2014            |          |
| Time increase factor (f)  | 0,9      |
| Energy Efficiency (EElhood)   | 52,3     |
| Measured air flow rate at best efficiency point (QBEP)(m³/h)                      | 330,0    |
| Measured air pressure at best efficiency point (PBEP)(Pa)                         | 436      |
| Measured electric power input at best efficiency point (WBEP)(W)                  | 133,2    |
| Nominal power of the lighting system (WL)(W)                                      | 6,0      |
| Average illumination of the lighting system on the cooking surface (Emiddle)(lux) | 387      |