| Directive EU 65/2014 – EN61591, EN60704-2-13, EN50564 | |
|---|----------|
| Brand SILVERLINE Model SL 4117 - 80 SR BETA ADA | |
| Model SL 4117 - 80 SR | BETA ADA |
| Annual Energy Consumption (AEC)(kWh/a) | 48,1 |
| Energy Efficiency Class (EEI) | Α |
| Fluid Dynamic Efficiency(FDE) | 30,0 |
| Fluid Dynamic Efficiency class (FDE) (Indice) | Α |
| Light Efficiency (LE) | 64 |
| Lighting Efficiency Class (LE)(indice) | Α |
| Grease Filtering Efficiency (GFE) | 76,0 |
| Grease Filtering Efficiency Class (GFE)(indice) | С |
| Minimum Air Flow in Normal Use MIN (m³/h) | 248 |
| Maximum Air Flow in Normal Use (intensive / boost excluded) MAX (m³/h) | 642 |
| Air Flow at Intensive/Boost Setting (m³/h) | - |
| Sound Power Level at Minimum Speed Avaible in Normal Use MIN (LWA)(dB) | 45 |
| Sound Power Level at Maximum Speed Avaible in Normal Use MAX (LWA)(dB) | 66 |
| Sound Power Level at Intensive/Boost Setting (LWA)(dB) | - |
| Power Consuption Off Mode (Po)(W) | 0,40 |
| Power Consuption in Standby Mode (Ps)(W) | - |
| Product Information compliant to commission regulation (EU) No 66/2014 | • |
| Time increase factor (f) | 0,9 |
| Energy Efficiency (EElhood) | 52,3 |
| Measured air flow rate at best efficiency point (QBEP)(m³/h) | 330,0 |
| Measured air pressure at best efficiency point (PBEP)(Pa) | 436 |
| Measured electric power input at best efficiency point (WBEP)(W) | 133,2 |
| Nominal power of the lighting system (WL)(W) | 6,0 |
| Average illumination of the lighting system on the cooking surface (Emiddle)(lux) | 387 |