| Directive EU 65/2014 – EN61591, EN60704-2-1 | SILVERLINE |
|--|--------------|
| Model | SM 4380-50RF |
| Annual Energy Consumption (AEC)(kWh/a) | 92 |
| Energy Efficiency Class (EEI) | D |
| luid Dynamic Efficiency(FDE) | 6,9 |
| -luid Dynamic Efficiency class (FDE) (Indice) | F |
| .ight Efficiency (LE) | 37 |
| ighting Efficiency Class (LE)(indice) | A |
| Grease Filtering Efficiency (GFE) | 70,0 |
| Grease Filtering Efficiency Class (GFE)(indice) | D |
| ۱inimum Air Flow in Normal Use MIN (m³/h) | 154 |
| /Jaximum Air Flow in Normal Use (intensive / boost excluded) MAX (m³/h) | 298 |
| Air Flow at Intensive/Boost Setting (m ³ /h) | - |
| iound Power Level at Minimum Speed Avaible in Normal Use MIN (LwA)(dB) | 50 |
| ound Power Level at Maximum Speed Avaible in Normal Use MAX (LWA)(dB) | 64 |
| Sound Power Level at Intensive/Boost Setting (LWA)(dB) | - |
| Power Consuption Off Mode (Po)(W) | - |
| | 0,66 |
| Power Consuption in Standby Mode (Ps)(W) Product Information compliant to commission regu | |
| | 17 |
| ime increase factor (f) | 1,7 |
| nergy Efficiency (EElhood) | 98,0 |
| Neasured air flow rate at best efficiency point (QBEP)(m ³ /h) | 123,0 |
| | 279 |
| Neasured air pressure at best efficiency point (PBEP)(Pa) | |
| | 137,0 |
| Aeasured electric power input at best efficiency point (WBEP)(W) | 6,0 |
| Jominal power of the lighting system (WL)(W) | |
| Average illumination of the lighting system on the cooking surface (Emiddle)(lux) | 224 |