Directive EU 65/2014 – EN61591, EN60704-2-13, EN50564 Brand SILVERLINE	
Model SM 4386 - 40 SR	
Annual Energy Consumption (AEC)(kWh/a)	28,7
Energy Efficiency Class (EEI)	В
Fluid Dynamic Efficiency(FDE)	15,7
Fluid Dynamic Efficiency class (FDE) (Indice)	D
Light Efficiency (LE)	56
Lighting Efficiency Class (LE)(indice)	Α
Grease Filtering Efficiency (GFE)	75,9
Grease Filtering Efficiency Class (GFE)(indice)	С
Minimum Air Flow in Normal Use MIN (m³/h)	213
Maximum Air Flow in Normal Use (intensive / boost excluded) MAX (m³/h)	335
Air Flow at Intensive/Boost Setting (m <sup>3</sup> /h)	-
Sound Power Level at Minimum Speed Avaible in Normal Use MIN (LWA)(dB)	55
Sound Power Level at Maximum Speed Avaible in Normal Use MAX (LWA)(dB)	65
Sound Power Level at Intensive/Boost Setting (LWA)(dB)	-
Power Consuption Off Mode (Po)(W)	-
Power Consuption in Standby Mode (Ps)(W)	0,40
Product Information compliant to commission regulation (EU) No 6	6/2014
Time increase factor (f)	1,4
Energy Efficiency (EElhood)	63,6
Measured air flow rate at best efficiency point (QBEP)(m <sup>3</sup> /h)	168,7
Measured air pressure at best efficiency point (PBEP)(Pa)	164
Measured electric power input at best efficiency point (WBEP)(W)	49,1
Nominal power of the lighting system (WL)(W)	5,0
Average illumination of the lighting system on the cooking surface (Emiddle)(lux)	280

\*\*Product performance values are declared according to the measurements without carbon filter. It can be changes in the performance value according to the type of carbon filter to be used in the product.