Directive EU 65/2014 - EN61591, EN60704-2-13, EN505	64
Brand SILVERLINE	
Model PE 418	3-60 SORT
Annual Energy Consumption (AEC)(kWh/a)	44
Energy Efficiency Class (EEI)	<b>A</b> +
Fluid Dynamic Efficiency(FDE)	35,0
Fluid Dynamic Efficiency class (FDE) (Indice)	Α
Light Efficiency (LE)	50
Lighting Efficiency Class (LE)(indice)	А
Grease Filtering Efficiency (GFE)	76,1
Grease Filtering Efficiency Class (GFE)(indice)	С
Minimum Air Flow in Normal Use MIN (m³/h)	243
Maximum Air Flow in Normal Use (intensive / boost excluded) MAX (m³/h)	479
Air Flow at Intensive/Boost Setting (m³/h)	724
Sound Power Level at Minimum Speed Avaible in Normal Use MIN (LWA)(dB)	44
Sound Power Level at Maximum Speed Avaible in Normal Use MAX (LWA)(dB)	65
Sound Power Level at Intensive/Boost Setting (LWA)(dB)	71
Power Consuption Off Mode (Po)(W)	-
Power Consuption in Standby Mode (Ps)(W)	0,38
Product Information compliant to commission regulation (EU) No 6	6/2014
Time increase factor (f)	1,1
Energy Efficiency (EElhood)	42,3
Measured air flow rate at best efficiency point (QBEP)(m³/h)	412,1
Measured air pressure at best efficiency point (PBEP)(Pa)	474
Measured electric power input at best efficiency point (WBEP)(W)	155,0
Nominal power of the lighting system (WL)(W)	6,0
Average illumination of the lighting system on the cooking surface (Emiddle)(lux)	360