

Directive EU 65/2014 – EN61591, EN60704-2-13, EN50554

| | |
|---|--------------------------|
| Brand | SILVERLINE |
| Model | SM 3391-80HV OPAL |
| Annual Energy Consumption (AEC)(kWh/a) | 52 |
| Energy Efficiency Class (EEI) | A |
| Fluid Dynamic Efficiency(FDE) | 29,6 |
| Fluid Dynamic Efficiency class (FDE) (Indice) | A |
| Light Efficiency (LE) | 44 |
| Lighting Efficiency Class (LE)(indice) | A |
| Grease Filtering Efficiency (GFE) | 70,0 |
| Grease Filtering Efficiency Class (GFE)(indice) | D |
| Minimum Air Flow in Normal Use MIN (m ³ /h) | 229 |
| Maximum Air Flow in Normal Use (intensive / boost excluded) MAX (m ³ /h) | 582 |
| Air Flow at Intensive/Boost Setting (m ³ /h) | 750 |
| Sound Power Level at Minimum Speed Available in Normal Use MIN (LWA)(dB) | 42 |
| Sound Power Level at Maximum Speed Available in Normal Use MAX (LWA)(dB) | 64 |
| Sound Power Level at Intensive/Boost Setting (LWA)(dB) | 67 |
| Power Consumption Off Mode (Po)(W) | - |
| Power Consumption in Standby Mode (Ps)(W) | 0,22 |
| Product Information compliant to commission regulation (EU) No 66/2014 | |
| Time increase factor (f) | 0,9 |
| Energy Efficiency (EElhood) | 53,0 |
| Measured air flow rate at best efficiency point (QBEP)(m ³ /h) | 338,2 |
| Measured air pressure at best efficiency point (PBEP)(Pa) | 454 |
| Measured electric power input at best efficiency point (WBEP)(W) | 144,0 |
| Nominal power of the lighting system (WL)(W) | 6,5 |
| Average illumination of the lighting system on the cooking surface (Emiddle)(lux) | 283 |