

| Directive EU 65/2014 – EN61591, EN60704-2-13, EN50564 | |
|---|-----------------------|
| Brand | SILVERLINE |
| Model | PE 412-60 SORT |
| Annual Energy Consumption (AEC)(kWh/a) | 73 |
| Energy Efficiency Class (EEI) | C |
| Fluid Dynamic Efficiency(FDE) | 14,8 |
| Fluid Dynamic Efficiency class (FDE) (Indice) | D |
| Light Efficiency (LE) | 38 |
| Lighting Efficiency Class (LE)(indice) | A |
| Grease Filtering Efficiency (GFE) | 80,0 |
| Grease Filtering Efficiency Class (GFE)(indice) | C |
| Minimum Air Flow in Normal Use MIN (m ³ /h) | 268 |
| Maximum Air Flow in Normal Use (intensive / boost excluded) MAX (m ³ /h) | 530 |
| Air Flow at Intensive/Boost Setting (m ³ /h) | - |
| Sound Power Level at Minimum Speed Available in Normal Use MIN (LWA)(dB) | 51 |
| Sound Power Level at Maximum Speed Available in Normal Use MAX (LWA)(dB) | 65 |
| Sound Power Level at Intensive/Boost Setting (LWA)(dB) | - |
| Power Consumption Off Mode (Po)(W) | 0,41 |
| Power Consumption in Standby Mode (Ps)(W) | - |
| Product Information compliant to commission regulation (EU) No 66/2014 | |
| Time increase factor (f) | 1,5 |
| Energy Efficiency (EElhood) | 81,4 |
| Measured air flow rate at best efficiency point (QBEP)(m ³ /h) | 270,0 |
| Measured air pressure at best efficiency point (PBEP)(Pa) | 260 |
| Measured electric power input at best efficiency point (WBEP)(W) | 132,0 |
| Nominal power of the lighting system (WL)(W) | 3,0 |
| Average illumination of the lighting system on the cooking surface (Emiddle)(lux) | 114 |